Design of the Attitude and Orbit Control System for ESA's Solar Orbiter

Colin Maule and Andrew Pollard Tessella Ltd. MATLAB Expo Benelux, 20 June 2017



altran Part of the Altran Group



Overview

- Introduction to Tessella
- Our part in the Solar Orbiter programme
- Control Engineering with MathWorks
- Integrating MathWorks into large projects





Altran

essella

GLOBAL LEADER IN ENGINEERING AND INFORMATION SERVICES



23 countries

29k employees

300 of the Global 500 are clients

1.9 bn euros revenues

Industries: from **automotive** to **utilities**



Tessella, Altran's World Class Center for Analytics We use data science to accelerate evidence-based decision making

OPERATIONS						
UK, US, NL, FR, E	S					
DE, SE, PT						

essella

EXPERIENCE 30+ years of experience delivering 1000s of data

analytics projects

DNA Data is in our DNA. 250 of the brightest scientific minds, 50% hold PhDs

KNOWLEDGE

Unique combination of domain knowledge, data engineering expertise, maths & statistics excellence

altran Part of the Altran Group

Our work allows businesses to improve profitability, reduce costs, streamline operations, avoid errors and out-innovate the competition.



Predicting the best coatings for ships. Reducing fuel costs by up to 15%



Data analytics powers H3 Biosciences drug research. Reducing time to go from lab to clinic by 75%





Streamlining the creation of new oil wells . Saving BP \$100s of million



Helping Unilever's customers identify wholesome alternatives to existing preferences



Generating maps of disease risk in weeks not years. So medical intervention is better targeted

Tessella's part on Solar Orbiter





Fundamental AOCS requirements

- Get it where it needs to be
- Point it in the right direction
 - Keep it safe

Scale






Earth 1 AU: Dia= 1






ALTRAN Part of the Altran Group


Scope







Tessella's Part in the AOCS Subsystem





ALTRAN Part of the Altran Group

Control Engineering with Matlab & Simulink


Andrew Pollard Mathematical Modeller & Algorithm Developer Tessella Ltd.




altran Part of the Altran Group

Key Engineering Challenges

- Very extreme environment close to Sun
- Sun shield must remain pointed towards Sun, otherwise the heat will destroy the spacecraft
- Need to achieve precise trajectory for gravity assist manoeuvres









The Solution AOCS: Attitude and Orbit Control Subsystem

- Autonomously control angle of rotation around 3 axes to keep spacecraft correctly oriented and execute ground-commanded manoeuvres
- Perform orbit correction manoeuvres with thrusters
- A critical subsystem!







Spacecraft AOCS Hardware

Sensors

Fine Sun Sensor

Star Tracker

Measurement

Inertial

Unit


۲

Actuators

- **Reaction Control System** • (thrusters)
- **Reaction Wheels** ٠












The Attitude Control Loop



ALTRAN Part of the Altran Group



Design Challenges



FRAN Part of the Altran Group

- Very stringent autonomous pointing requirements for making scientific observations: *Equivalent to pointing at this screen for 10 seconds... from Greenland!* MATLAB & Control Systems Toolbox
- Flexible modes of appendages must not be excited
 Control Systems Toolbox & Signal Processing Toolbox
 - Very limited fuel
 - Complex system to model

Simulink

Optimization Toolbox




Autonomy


- "Safe modes" of AOCS need to be fully autonomous to recover quickly from hardware failure
- Any ground intervention occurs slowly can take ~ 10 minutes for signal to reach spacecraft
- Up to 70 days no comms at all during solar conjunction
- Required orbit corrections calculated by ground operations team, but manoeuvre is autonomous








- Control Systems Toolbox used to compute envelope of frequency responses in presence of uncertainty and variability.
 - Ensures spacecraft is stable with enough margin
 - > Robustness
- Signal Processing Toolbox for candidate flexure filters. Genetic algorithm to investigate parameter improvements






- In-house tools developed in MATLAB for repeated tasks, such as:
 - Constraint & sensitivity analysis
 - Automated controller tuning
 - Reporting of analysis results
- Allows rapid response to changes in inputs





- Optimization toolbox for thruster modulation proving 6-D control
 - Given force and torque demands, determine which thrusters to fire and for how long
 - Minimise fuel consumption








- Simulink for modelling full control loop, including hardware models
 - Rapid prototyping and design trade-offs
 - Verification of performance and robustness of control algorithms via Monte Carlo campaigns

Simulation of specific scenarios







Key Benefits of MathWorks-based Solutions

Benefits

- Control Systems toolbox for controller design
- Optimization toolbox for thruster modulation
- Simulink for modelling & simulation of full system

The industry benchmark. Nothing else comes close for control engineering

Attitude control will use only 40 kg propellant in 10 years

No other tool gives us the multidomain simulation capability and block diagram environment in a way that is scalable to represent complex systems. That is why we use Simulink.



ALTRAN Part of the Altran Group

Integrating MathWorks into Large Projects





Further Challenges

- Schedule
 - Changing the launch date is major!
- Knowledge transfer in a changing project team
- Large-scale system design problem
 - SW alone has 100s of tuneable
 - parameters
 - Cannot be held in the head of 1 person!





Running the Project

- Very large collection of MATLAB code for long-term internal use by a large team
- Rigorous software engineering practices & tools appropriate for maintaining this code:
 - Bitbucket for distributed Git version control to promote code review, linked to CI server
 - JIRA Issue Tracking System linked to version control
 - TeamCity Continuous Integration for automated tests, and longrunning analyses / simulations

essella

·	Design / Modes / NCM / +NcmTuning / AttitudeController_Transition.m	OUTDATE
CTIONS		
Clone	9 37 function this = AttitudeController Transition()	
	10 - this = this@NcmBase.AttitudeControllerTuning_LagLead();	
Create branch	<pre>38 + this = this@ProcessedConstraintSetAnalysis();</pre>	
Create pull request	11 39 12 40 this.submode = senum NcmSubmode.NCM T:	
	12 40 this.submode = senum [KemSubmode.NCM_T] 13 41 this.com/ig sc = { 'Operational', 'IBoom DEP', 'IBoom STO'};	
C Fork	14 42	
	15 - this.optimisationArgs = {@(wX,wL)calculateSettlingTime(wL,wX,exp(-1)), 'min'};	
Reports	43 + this.labelNames = {'K_d', 'K_p'};	
	44 + this.parameterUnits = ('/s', '/s^2'); 45 + this.optimisationArgs = {'K p', 'max', 'K d', 'max'};	
AVIGATION	Andrew Pollard	
	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan	t. Which is mor
		t. Which is mor
Overview	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan	t. Which is mor
	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here?	t. Which is mor
Overview	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here?	t. Which is mor
Overview	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Repty · Edit · Create task · 02 Jun 2016	
Overview	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Reply · Edit · Create task · 02 Jun 2016	
Overview Source Commits Graphs	 Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Roply - Edit - Create task - 02 Jun 2016 west Good point. For now, I had just set it so that it matches what's done for SASM. But for NCM-T and particularly the rate settling the set of the set	
Overview Source Commits	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Roply - Edit - Create task - 02 Jun 2016	
Overview Source Commits Graphs	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Roply - Edit - Create task - 02 Jun 2016	
Overview Source Commits Graphs Branches	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constan driving here? Roply - Edit - Create task - 02 Jun 2016 west Good point. For now, I had just set it so that it matches what's done for SASM. But for NCM-T and particularly the rate settling to more sense to maximise Kd. TII change this now. Roply - Create task - Use - 02 Jun 2016	
Overview Source Commits Graphs Branches	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constant driving here? Reply - Edit - Create task - 02 Jun 2016 west Good point. For now, I had just set it so that it matches what's done for SASM. But for NCM-T and particularly the rate settling to more sense to maximise Kd. TII change this now. Reply - Create task - Like - 02 Jun 2016 James Myatt For SASM at least, maximising K_d is achieved by setting K_p to zerol	
Source Commits Graphs Branches Network	Is this the best order to optimise? I think maximising Kp minimises the attitude offset, while maximising Kd minimises the time constant driving here? Reply - Edit - Create task - 02 Jun 2016 west Good point. For now, I had just set it so that it matches what's done for SASM. But for NCM-T and particularly the rate settling to more sense to maximise Kd. TII change this now. Reply - Create task - Like - 02 Jun 2016 James Myatt	





altran Part of the Altran Group

Benefits of Continuous Integration

We used continuous integration to:

- Automatically run unit tests & integration tests daily to check impact of code changes
- Help with configuration management of delivered files
- Run simulation campaigns on a server at the press of a button
- Run lengthy analyses and enable configuration management of the results
 - Improved response time & verification


Projects ∣ ⊂ Changes	Agents 🧃 📄 Build Queue 🕧		[13] An	drew Pollard		
6792 - SOLO				0	Hide Suce	cessful Configurat
Overview Change Log Statistics	Current Problems Investigatio	ns Muted Problems	Build Chains			
Experimental Builds						
Generic Functions					2 successful	
Simulations						
Generic IV					2 successful	
▶ 🖻 NCM 🗠				1 failing	10 successful	
MOO III III					5 successful	
▶ 🖻 SASM 🗠				1 failing	6 successful	
▶ 🖻 WSM 🗠					3 successful	
🔻 🖻 Solar Orbiter AOCS 👓						
CAS Checks	Tests: 😣 6		Pending (8)			Idle Run
Code Quality - Atomi	⊲ Þ					Idle Run
Code Quality - Mathy	vorks IV					Idle Run
V 🔲 OSE Checks 🔍						Run
develop #1285.92ef1a6	Tests passed: 3	Artifacts ♥	James Myatt (1) ♡	4	months ago (16m:	02s)
▼ 🗏 Unit tests (All) ▽						Run
develop #3002.92ef1a6	Tests failed: 19, passed: 5283, mutod: 3 las	Artifacts 🗢	James Myatt (1) I		4 months ago (2h:5	53m)



Object-Oriented Programming in MATLAB

- Improve traceability of a parameter by storing metadata in an object, e.g.
 - where the value is documented
 - in which database version was it last changed
 - which program calculated it, etc.
- Automatic unit conversions reduce the occurrence of mistakes & hardcoded numbers
- Other uses of OOP included standardising how tuning & analysis functions are used
 - Easy to learn how to update documents

essella




```
ans =
```

ParameterValue

```
name: Design.SASM.Objective.LOS.sigma ang ctrl farSun
design ref: <u>calculateSASMPointingObjectiveLOS</u>
reference: SASM Tuning and Stability Analysis (SOL.S.ASTR.TN.00373 2 draft)
source: Objectives / DesignDB_SASM v4_01.xml
version: 4.1
author: TESSELLA
status: Derived
datatype: double
value [rad]:
0.0116
value [deg]:
0.6655
```




Lessons Learnt




- Results of complex analyses require high level of traceability
 - E.g. "Which parameters were used to produce these results from 2 years ago?"
 - Traceability requires configuration management
 - Continuous integration supports this
- Review of code, models & analysis has high value even if not deliverable
 - Everyone's work is reviewed, and everyone reviews work
- Document your modelling assumptions
 Turn into tests where possible





The Project Today

- Tessella's key deliveries are complete
- Detailed testing of AOCS algorithms being carried out by Airbus DS; we continue providing support
- Next stop... THE SUN!








Summary

- Solar Orbiter is an exciting ESA mission at the forefront of science, and a very complex engineering challenge
- Tessella made good use of MATLAB & Simulink to develop the algorithms for one of Solar Orbiter's key autonomous control systems
- Supporting tools and good software engineering practices were also used to get the best out of MATLAB on a large project, and these practices can be used in other domains







Further information


- MATLAB File Exchange www.mathworks.com/matlabcentral/fileexchange/
- Solar Orbiter sci.esa.int/solar-orbiter/
- Tessella

Come and see our stand at the expo! https://tessella.com/

 MathWorks Training Services www.mathworks.com/services/training.html







Questions



